

SAFETY DATA SHEET



according to 1907/2006/EC, Article 31

Plasticast (R) PT investment

Page 1/7

Revision 0 Revision date 2015-10-29

SECTION 1: Identification of the substance/mixture and of the company/undertaking				
1.1. Product identifier Prod	duct Part Number: Z14-304-PT50			
Product name	Plasticast (R) PT investment			
Product code	Plasticast (R) PT investment 020817 R506			
1.2. Relevant identified uses of t	he substance or mixture and uses advised against			
Description	Foundry material.			
1.3. Details of the supplier of the	safety data sheet			
Company	Romanoff International Supply Corporation			
Address	9 Deforest Street, Amityville, NY 11701 USA. Tel: 631-842-2400			
Web Telephone Fax Email Email address of the	www.romanoff.com +1 (631) 842-2400 +1 (631) 842-0028 sales@romanoff.com			
competent person				
1.4. Emergency telephone numb				
Emergency telephone number Company	CHEMTEL, ACCOUNT #MIS4594445 COLLECT CALLS ACCEPTED USA, CANADA 1-800-255-3924 AUSTRALIA: 1-300-954-583 BRAZIL: 0-800-591-6042 CHINA: 400-120-0751 INDIA: 000-800-100-4086 MEXICO: 01-800-099-0731 ALL OTHER COUNTRIES: 1-813-248-0585 Collection Collection			

SECTION 2: Hazards identifi	cation				
2.1. Classification of the substance or mixture					
2.1.2. Classification - EC 1272/2008	arc. 1A: H350; STOT RE 1: H372;				
2.2. Label elements					
Hazard pictograms	This substance / mixture has been classified in accordance with the US Federal OSHA Hazard Communication Standard 29CFR 1910.1200. Substance concentration band-ranges are presented, and minor ingredient compostion maybe withheld, to protect trade secrets.				
Signal Word	Danger				
Hazard Statement	Carc. 1A: H350 - May cause cancer inhalation. STOT RE 1: H372 - Causes damage to organs (lungs) through prolonged or repeated exposure inhalation.				
Precautionary Statement: Prevention	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood.				



0

Revision date 2015-10-29

Revision

2.2. Label elements	
	 P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P264 - Wash (hands) thoroughly after handling. P270 - Do no eat, drink or smoke when using this product. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P285 - In case of inadequate ventilation wear respiratory protection.
Precautionary Statement: Response	P308+P313 - IF exposed or concerned: Get medical advice/attention. P314 - Get medical advice/attention if you feel unwell.
Precautionary Statement: Storage	P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to local and national regulations
2.3. Other hazards	
Other hazards	Product contains crystalline silica.
Further information	
	Not applicable. PBT and vPvB assessment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration	Conc. (%w/w)	Classification	M-factor.
Magnesium Oxide		01309-48-4	215-171-9			xn; R20 Xi; R37/38	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
silica (cristobalite conc. >/= 1.0 %))	14464-46-1	238-455-4		40 - 50%	Carc. 1A: H350; STOT RE 1: H372;	
quartz (conc. >/= 1.0%)		14808-60-7	238-878-4		30 - 40%	Carc. 1A: H350; STOT RE 1: H372;	
Mono ammonium phosphate		7722-76-1	231-764-5		1 - 10%		
Magnesium Oxide		01309-48-4	215-171-9		1 - 10%		

Further information

Full text for all Risk Phrases mentioned in this section are displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.		
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.		
Skin contact	Wash with soap and water.		
Ingestion	Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING.		
4.2. Most important symptoms a	nd effects, both acute and delayed		
Inhalation	May cause irritation to respiratory system.		
Eye contact	May cause irritation to eyes.		
Skin contact	May cause irritation to skin.		
Ingestion	May cause irritation to mucous membranes.		
4.3. Indication of any immediate medical attention and special treatment needed			
Inhalation	Seek medical attention if irritation or symptoms persist.		
Eye contact	Seek medical attention if irritation or symptoms persist.		

	Revision date 2015-10-29
4.3. Indication of any immediate	medical attention and special treatment needed
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention if irritation or symptoms persist.
SECTION 5: Firefighting mea	asures
5.1. Extinguishing media	
	Use extinguishing media appropriate to the surrounding fire conditions.
5.2. Special hazards arising from	n the substance or mixture
	Burning produces irritating, toxic and obnoxious fumes.
5.3. Advice for firefighters	
	Self-contained breathing apparatus. Wear suitable protective clothing.
SECTION 6: Accidental relea	ase measures
6.1. Personal precautions, prote	ctive equipment and emergency procedures
	Avoid raising dust. Wear suitable respiratory equipment when necessary.
6.2. Environmental precautions	
	No environmental requirements.
6.3. Methods and material for co	ntainment and cleaning up
	Avoid raising dust. Clean the area using a vacuum cleaner. Transfer to suitable, labelled containers for disposal.
6.4. Reference to other sections	
	See section [2, 8 & 13] for further information.
SECTION 7: Handling and st	torage
7.1. Precautions for safe handlin	g
	Avoid raising dust. Ensure adequate ventilation of the working area. In case of insufficient ventilation, wear suitable respiratory equipment.
	Do not eat, drink or smoke in areas where this product is used or stored. Wash hands after handling the product.
7.2. Conditions for safe storage,	including any incompatibilities
	Keep containers tightly closed.
7.3. Specific end use(s)	
	Foundry material.
SECTION 8: Exposure contr	ols/personal protection
8.1. Control parameters	
	exposure limits - Crystalline Silica, Cristobalite - 0.025 mg/m3 TWA ACGIH TLV (respirable fraction); 10 mg/m3 / [2(% Silica + 2)] TWA PEL (respirable fraction).
	exposure limits - Crystalline Silica, quartz - 0.025 mg/m3 TWA ACGIH TLV (respirable fraction); 10 mg/m3 / (% Silica + 2) TWA PEL (respirable fraction).
8.2. Exposure controls	
8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Protective clothing.
Eye / face protection	In case of splashing, wear:. Approved safety goggles. safety glasses with side-shields.



 Revision
 0

 Revision date
 2015-10-29

8.2. Exposure controls	
Skin protection - Handprotection	Wear suitable gloves.
Respiratory protection	Suitable respiratory equipment.
8.2.3. Environmental exposure controls	Not normally required.
Occupational exposure controls	Appropriate local exhaust ventilation is required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Powder
	Off white
	Slight
	2.38 (H2O = 1 @ 20 °C)
Partition coefficient	
	No data available
•	No data available
•••	No data available
Explosive properties	
Oxidising properties	
••••	Not applicable.
Initial boiling point	
Evaporation rate	
Flammability (solid, gas)	
Vapour pressure	
	Not applicable.
Autoignition temperature	
• .	Not applicable.
-	
SoluBility	Slightly soluble in water

9.2. Other information

Conductivity	No data available
Surface tension	Not applicable.
Benzene Content	Not applicable.
VOC (Volatile organic	Not applicable.
compounds)	
Lead content	Not applicable.

SECTION 10: Stability and reactivity

10.1. Reactivity

	Not applicable.			
10.2. Chemical stability				
	Stable under normal conditions.			
10.3. Possibility of hazardous reactions				
	No Significant Hazard.			
10.4. Conditions to avoid				
	Moisture.			
10.5. Incompatible materials				
	No Significant Hazard.			

Revision 0 Revision date 2015-10-29

10.6. Hazardous decomposition products

Hazardous Decomposition Products (silica): Crystalline silica will dissolve in hydro	ofluoric acid
and produce silicone tetrafluoride. Reaction with water or acids generates heat.	

SECTION 11: Toxicological information

11.1. Information on toxicological effects	
Acute toxicity	Based on available data, the classification criteria are not met.
Skin corrosion/irritation	Prolonged or repeated exposure may cause irritation to skin and mucous membranes.
Serious eye damage/irritation	No irritation expected.
Respiratory or skin sensitisation	No sensitizaton effects reported.
Germ cell mutagenicity	No mutagenic effects reported.
Carcinogenicity	Known Human Carcinogens (Category 1).
Reproductive toxicity	No observed effect level. No observed effect concentration.
STOT-single exposure	No known adverse health effects.
STOT-repeated exposure	Chronic effects Prolonged inhalation of respirable crystalline silica In 1997, the International Agency for Research on Cancer (IARC) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibers, 1997, Vol. 68, IARC, Lyon, France). In June 2003, the European Commission's Scientific Committee for Occupational Exposure Limits (SCOEL) concluded: "that the main effect in humans of the inhalation of respirable crystalline silica is silicosis. There is sufficient information to conclude that the relative lung cancer risk is increased in persons with silicosis (and apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk. Since a clear threshold for silicosis development cannot be identified, any reduction of exposure will reduce the risk of silicosis."
	(SCOEL SUM Doc 94-final on respirable crystalline silica, June 2003) There is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required (see Section 16).
Aspiration hazard	No Significant Hazard.
Repeated or prolonged exposure	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.

SECTION 12: Ecological information

12.2. Persistence and degradability

No data is available on this product.

12.3. Bioaccumulative potential

Does not bioaccumulate.

Partition coefficient

Plasticast (R) PT investment No data available

12.4. Mobility in soil

Not determined.

12.5. Results of PBT and vPvB assessment



	Revision date 2015-10-2
12.5. Results of PBT and vPvB	assessment
	Not determined.
12.6. Other adverse effects	
	Not applicable.
SECTION 13: Disposal cons	siderations
13.1. Waste treatment methods	
	Dispose of in compliance with all. local and national regulations.
Disposal methods	
	Contact a licensed waste disposal company.
Disposal of packaging	1
	Empty containers can be sent for disposal or recycling.
SECTION 14: Transport info	prmation
Further information	
	The product is not classified as dangerous for carriage.
SECTION 15: Regulatory int	formation
15.1. Safety, health and enviror	mental regulations/legislation specific for the substance or mixture
Regulations	U.S. FEDERAL REGULATIONS:
	CERCLA 103 Reportable Quantity: Plasticast PT investment is not subject to CERCLA reporting requirements. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.
	SARA TITLE III: Hazard Category For Section 311/312: Chronic health
	Section 313 Toxic Chemicals: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None
	Section 302 Extremely Hazardous Substances (TPQ): None
	EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.
	U.S. STATE REGULATIONS
	California Proposition 65: This product contains the following substances known to the State of California to cause cancer: Crystalline Silica as Quartz and Cristobalite (< 90 %);
	INTERNATIONAL REGULATIONS:
	Canadian Environmental Protection Act: All of the components in this product are listed on the Domestic Substances List (DSL).
	Canadian WHMIS Classification: Class D2A (Chronic toxic effects), D2A (Carcinogenicity).

No data is available on this product.

SECTION 16: Other information



 Revision
 0

 Revision date
 2015-10-29

Other information	
Text of risk phrases in Section 3	R20 - Harmful by inhalation. R37/38 - Irritating to respiratory system and skin.
Text of Hazard Statements in Section 3	Carc. 1A: H350 - May cause cancer . STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure .
Further information	
	Training Workers must be informed of the presence of crystalline silica and trained in the proper use and handling of this product as required under applicable regulations.
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

