

## **SAFETY DATA SHEET**

### **1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

**Product Identification**

Product Name: FAST CAST Working Solution - Liquid  
Product Number: 2937, 2937S, 2937-5  
Chemical Name: Silica  
CAS Number: Blend

**Company Identification**

Romanoff International  
9 Deforest Street  
Amityville New York 11701 USA  
Phone: 1-631-842-2400 , Fax: 631-842-0028

**Emergency Contact:** CHEMTEL, ACCOUNT #MIS4594445 COLLECT CALLS ACCEPTED 24 HR EMERGENCY  
TELEPHONE: USA, CANADA, PUERTO RICO & US VIRGIN ISLANDS 1-800-255-3924  
AUSTRALIA: 1-300-954-583 BRAZIL: 0-800-591-6042 CHINA: 400-120-0751 INDIA:  
000-800-100-4086 MEXICO: 01-800-099-0731 ALL OTHER COUNTRIES: 1-813-248-0585

### **2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW:**

WARNING: Causes eye and skin irritation. Harmful or fatal if swallowed. May be absorbed through the skin.  
Inhalation may cause respiratory irritation. Prolonged overexposure may cause lung, liver and kidney damage.  
Contains ethylene glycol, which may cause birth defects based on animal studies.

**GHS Classification:**

Carcinogenicity - Category 1  
Respiratory or skin Sensitization - Category 1

**GHS Hazard Symbols:**

Irritant, Health Hazard

**EYE:**

Causes eye irritation.

**SKIN:**

Causes skin irritation.

**INHALATION:**



Causes respiratory tract irritation.

**INGESTION:**

Ingestion is not considered a potential route of exposure.

**CHRONIC EFFECTS:**

Prolonged exposure may cause delayed injury to the pulmonary system.

**CARCINOGENICITY INFORMATION:**

None of the components of this product are listed as carcinogens by OSHA, IARC, NTP or the EU Directives.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:**

Individuals with pre-existing skin, respiratory, liver and kidney disease may be at increased risk from exposure.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**COMPONENT LISTING:**

**Chemical Name**

SILICA COLLOIDAL ETHYLENE GLYCOL

This product contains hazardous materials as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

As defined under Sara 311 and 312, this product contains materials that are acute, chronic hazards.

### 4. FIRST AID MEASURES

**EYE CONTACT FIRST AID:**

In case of contact, immediately flush eyes with plenty of water, lifting upper and lower lids, for at least 15 minutes. Get immediate medical attention.

**SKIN CONTACT FIRST AID:**

Wash skin with soap and water. If irritation develops get immediate medical attention.

**INHALATION FIRST AID:**

If inhaled, remove to fresh air. If breathing is difficult, have qualified personnel administer oxygen. Get immediate medical attention.

**INGESTION FIRST AID:**

Ingestion is not considered a potential route of exposure. If ingested, do not induce vomiting. Give 2 glasses of water and get immediate medical attention.

### 5. FIRE FIGHTING MEASURES

**FLAMMABLE PROPERTIES**

COC Flash Point: N/A Autoignition

Temperature: N/A



**FLAMMABLE LIMITS IN AIR**

LEL: N/A  
UEL: N/A

**FLAMMABLE PROPERTIES:**

Not flammable under normal conditions.

**EXTINGUISHING MEDIA:**

Use water spray, dry chemical, alcohol foam and carbon dioxide. Cool fire exposed containers and structures with water. Do not direct a solid stream of water or foam into hot burning pools of liquid. This may cause frothing and increase fire intensity.

**FIRE & EXPLOSION HAZARDS:**

Closed containers may explode if exposed to extreme heat. Sudden release of hot organic chemical vapor from processing equipment operating at an elevated temperature and pressure or a sudden ingress of air into hot equipment under a vacuum may result in ignition without a source of ignition.

**FIRE FIGHTING INSTRUCTIONS:**

Firefighters should wear full emergency equipment and NIOSH approved positive pressure self-contained breathing apparatus. Do not allow run-off from fire fighting to enter drains or water courses.

**COMBUSTION PRODUCTS:**

Carbon monoxide and carbon dioxide.

## 6. ACCIDENTAL RELEASE MEASURES

**LARGE SPILLS PROCEDURE:**

Dike and contain spill with absorbent material such as clay or commercial sorbents. Store reclaimed material in DOT approved container for disposal.

Wear respirator and protective clothing as appropriate. Shut off source of leak. Dike & contain.

**SMALL SPILLS PROCEDURE:**

Same as large spill.

## 7. HANDLING AND STORAGE

**HANDLING (PERSONNEL):**

Avoid contact with the eyes, skin and clothing. Avoid breathing vapors. Wear protective clothing and equipment as described in Section 8. Use with adequate ventilation. Wash thoroughly with soap and water after handling. Keep containers closed when not in use.

When heated above 240C, thermal degradation may result in the formation of harmful volatile organic decomposition products which may require respiratory protection.

**HANDLING (PHYSICAL ASPECTS):**

Do not reuse containers. Empty containers retain product residues can be hazardous. Follow all SDS precautions when handling empty containers.

**STORAGE PRECAUTIONS:**

Store in a cool dry place away from incompatible materials. Protect from physical damage.



## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### EYE / FACE PROTECTION REQUIREMENTS:

Use safety glasses with side shields or chemical splash goggles.

### SKIN PROTECTION REQUIREMENTS:

Wear impermeable gloves.

### RESPIRATORY PROTECTION REQUIREMENTS:

If exposure exceeds exposure limits, use NIOSH approved respirator.

### MISCELLANEOUS:

Use general or local ventilation.

### EXPOSURE GUIDELINES:

#### SILICA, COLLOIDAL

OSHA Ceiling Limit: 20 ppm, 80 mg/m<sup>3</sup>

#### ETHYLENE GLYCOL

OSHA TWA: 50 ppm, 127 mg/m<sup>3</sup>

## 9. PHYSICAL AND CHEMICAL PROPERTIES

FORM:	Liquid
COLOR:	Translucent No
ODOR:	odor
BOILING POINT:	212 F
SOLUBILITY IN WATER:	Dispersible 1.2
SPECIFIC GRAVITY:	(Water = 1)

## 10. STABILITY AND REACTIVITY

### STABILITY:

Stable.

### POLYMERIZATION:

Product will not undergo polymerization.

### INCOMPATIBILITY WITH OTHER MATERIALS:

Avoid contact with reactive metals such as aluminum.

## 11. TOXICOLOGICAL INFORMATION

### EYE EFFECTS:

Contact may cause irritation with redness, tearing and swelling, May also cause temporary blurred or hazy vision.

### SKIN EFFECTS:

Contact may cause irritation, particularly on prolonged contact.



**ACUTE ORAL EFFECTS:**

Ingestion may cause mucous membrane and gastrointestinal irritation, abdominal pain, nausea, vomiting, dizziness, drowsiness, blurring of vision, lumbar pain and nervous system effects including irregular eye movements, confusion, collapse, convulsion and coma. Cardiac failure, pulmonary edema and severe kidney damage may develop. Liver damage may occur. May be fatal.

**ACUTE INHALATION EFFECTS:**

Inhalation of mist may cause mucous membrane and respiratory irritation. High vapor concentrations may produce headache, nausea, dizziness and irregular eye movements.

**CHRONIC EFFECTS /:**

Prolonged occupational overexposure may cause effects on the nervous system and lung damage. Ethylene glycol has been found to cause birth defects in studies with laboratory animals.

## 12. ECOLOGICAL INFORMATION

No information available.

## 13. DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL:**

Dispose of waste material in accordance with all local, state/provincial, and national requirements.

## 14. TRANSPORT INFORMATION

PRODUCT LABEL:	FAST CAST Working Solution - Liquid
D.O.T. SHIPPING NAME:	Non-flammable liquid
TECHNICAL SHIPPING NAME:	N/A
D.O.T. HAZARD CLASS:	N/A
UN NUMBER:	N/A

## 15. REGULATORY INFORMATION

**REGULATORY LISTS SEARCHED:**

01 = SARA 313

02 = CA Proposition 65



03 = SARA 302/304  
05 = ACGIH TWA  
07 = ACGIH CALC TLV  
09 = CANADIAN WHMIS  
11 = TSCA

04 = CERCLA 302.4  
06 = ACGIH STEL  
08 = OSHA PEL  
10 = OSHA Ceiling

**EEC Symbols and Indications of Danger:**

Harmful (Xn), Irritant (Xi)



**R-Phrases:**

R36/38 - Irritating to eyes and skin.  
R37 - Irritating to respiratory system.  
R20 - Harmful by inhalation.  
R22 - Harmful if swallowed.

**S-Phrases:**

S3/9 - Keep in a cool, well-ventilated place.

**WHMIS Hazard Symbols:**

Class D2 - Materials Causing Other Toxic Effects



**Canadian Disclosure List**

SILICA, COLLOIDAL (7631-86-9)  
ETHYLENE GLYCOL (107-21-1)

**SARA Title III - Section 313**

FAST CAST Working Solution - Liquid (BLEND) –  
ETHYLENE GLYCOL (107-21-1)

**Title V**

ETHYLENE GLYCOL (107-21-1)

**SC Toxic Air Pollutants List**

ETHYLENE GLYCOL (107-21-1)

**MISCELLANEOUS INFORMATION:**

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substance Control Act (TSCA).

## 16. OTHER INFORMATION



**HMIS Rating:**

Health - 1  
Flammability - 0  
Reactivity - 0

**ABBREVIATIONS USED IN THIS MSDS:**

TLV - THRESHOLD LIMIT VALUE  
STEL - SHORT TERM EXPOSURE LIMIT  
RQ - REPORTABLE QUANTITY  
C - CEILING LIMIT  
NDA - NO DATA AVAILABLE

TWA - Time Weighted Average  
TPQ - Threshold Planning Quantity  
PEL - Permissible Exposure Limit  
CAS - Chemical Abstract Service Number  
N/A - Not Applicable or Not Available

\*\*\*\*\*

\*\*\*\*\*

**END OF SAFETY DATA SHEET**

\*\*\*\*\*

