

Material Safety Data Sheet

MSDS No. 73-053A, 73-052, 73-052-5

Date Of Preparation: May 2, 2005

Revision: 0001

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: LMR - Liquid Mold Rubber

Manufacturer: Romanoff International, 9 Deforest St., Amityville, NY 11701

Phone (631) 842-2400, FAX (631) 842-0028

Emergency Contact: Chem-Tel

Domestic 800-255-3924

International 813-248-0585

Section 2 - Composition / Information on Ingredients

| Component | CAS Number | ACGIH TWA | Exposure Limits OSHA PEL | Weight Percent (%) |
|---------------------------------------|------------|------------------|--------------------------|--------------------|
| Butyl benzyl phthalate | 85-68-7 | None Established | None Established | 40-70 |
| Polymethylene polyphenyl isocyanate | 9016-87-9 | None Established | None Established | 15-25 |
| 4, 4' Methylene bis(phenylisocyanate) | 101-68-8 | 0.005 ppm | 0.02 ppm | 25-40 |

Section 3 - Hazards Identification

Potential Health Effects

| HMIS | |
|------|---|
| H | 2 |
| F | 1 |
| R | 1 |

Primary Entry Routes: Inhalation and Dermal

Target Organs: Lungs skin

Acute Effects Inhalation: Vapors are minimal due to low vapor pressure; if sprayed as an aerosol excessive concentrations are attainable that could be hazardous on single exposure.

Excessive exposure can cause irritation to respiratory tract and irritation of the eyes. Effects may be delayed. Decreased ventilatory capacity has been associated with exposure to similar isocyanates.

Eye: May cause irritation, redness, tearing, and blur vision. Prolonged vapor contact may cause conjunctivitis.

Skin: Contact will cause irritation, reddening, swelling, rash, scaling or blistering. Prolonged or repeated contact can cause moderate dermatitis.

Ingestion: May have corrosive effects on the linings of the mouth and stomach: symptoms can include sore throat, abdominal pain, nausea, vomiting and diarrhea.

Carcinogenicity: IARC, NTP, and OSHA do not list any components of this product as a carcinogen.

Medical Conditions Aggravated by Long-Term Exposure: skin allergies and respiratory disorders.

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.

Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact: In case of skin contact, wash thoroughly with soap and water; remove contaminated clothing and launder before reuse; seek medical attention if rash develops.

Section 4 - First Aid Measures (continued)

Ingestion: Do not induce vomiting unless instructed by a physician. Contact physician immediately

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

Flash Point: 390°F (200°C)

Flash Point Method: COC

Flammability Classification: Non-Flammable

Extinguishing Media: Water Fog, Dry Chemical, and Carbon Dioxide Foam

Unusual Fire or Explosion Hazards: Hazardous decomposition products may be formed. Avoid water contamination in closed containers or confined areas as exothermic heat and carbon dioxide can evolve.

Fire-Fighting Instructions: Fire fighters should wear self-contained breathing apparatus. Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.



Section 6 - Accidental Release Measures

Spill /Leak Procedures: Only properly protected personnel should remain in the spill area; dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - Handling and Storage

Handling Precautions: Minimize breathing of vapors and avoids prolonged or repeated contact with skin. Wear proper protective equipment. If ventilation is not sufficient, wear proper respiratory equipment. Avoid moisture contamination. Reseal partial containers. Use good general housekeeping procedures.

Storage Requirements: Store in cool dry, well-ventilated area.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls:

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Administrative Controls:

Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear an MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Section 8 - Exposure Controls / Personal Protection (continued)

Protective Clothing/Equipment: Wear chemically protective gloves, boots, and aprons to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics

Section 9 - Physical and Chemical Properties

Physical State: Liquid

Appearance : Brown liquid

Odor : Characteristic odor

Vapor Pressure: <0.00001 @ 25°C

Vapor Density (Air=1): 8.6

Specific Gravity (H₂O=1, at 4 °C): 1.10

Water Solubility: Negligible:

Boiling Point: None Determined

% Volatile: Nil

Freezing/Melting Point: None Determined

Viscosity: 1 poise

Evaporation Rate: Not Applicable

Section 10 - Stability and Reactivity

Stability: This product is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization can occur.

Chemical Incompatibilities: Strong bases, water, amines, alcohols.

Conditions to Avoid: Avoid contamination with water and other materials that react with Isocyanates.

Hazardous Decomposition Products: MDI vapors, hydrogen cyanide gas, oxides of nitrogen, carbon monoxide and carbon dioxide.

Section 11- Toxicological Information

Eye Effects: Irritation

Skin Effects: Irritation

Mutagenicity: None Determined

Teratogenicity: None Determined

Section 12 - Ecological Information

None Established

Section 13 - Disposal Considerations

Disposal: This material must be disposed of in accordance with applicable Federal, state and local regulations.

Section 14 - Transport Information

| DOT | IATA | IMDG |
|--|--|---|
| Shipping Name: Butyl Benzyl Phthalate Mixture (Greater than 100 pounds of Butyl Benzyl Phthalate) UN #: 3082 Hazard Class: 9 Label: Miscellaneous | Shipping Name: Butyl Benzyl Phthalate Mixture (Greater than 100 pounds of Butyl Benzyl Phthalate) UN #: 3082 Hazard Class: 9 Label: Miscellaneous | Shipping Name: Butyl Benzyl Phthalate Mixture UN #: 3082 Hazard Class: 9 Label: Marine Pollutant |

Section 15 - Regulatory Information

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

CERCLA Hazardous Substance (40 CFR 302.4) listed specific per RCRA, Sec. 3001; CWA, Sec. 311 (b)(4); CWA, Sec. 307(a), CAA, Sec. 112

| <u>Chemical Name</u> | <u>RQ</u> | <u>% Reportable Component</u> |
|------------------------|-----------|-------------------------------|
| Butyl Benzyl Phthalate | 100 lbs. | 70.0 Max |

SARA Toxic Chemical (40 CFR 372.65): None

This product contains the following chemicals that are subject to release reporting requirements under **section 313 of SARA Title III.**

| <u>Chemical Name</u> | <u>CAS #</u> | <u>% by Weight</u> |
|--|--------------|--------------------|
| 4, 4' Methylene bis (phenylisocyanate) | 101-68-8 | 40.0 Max |
| Polymethylene polyphenyl isocyanate | 9016-87-9 | 25.0 Max |

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): None

Clean Air Act

SOCMI Chemical: 4, 4' Methylene bis(phenylisocyanate) Hap Code: XOV

TSCA Inventory Status (40 CFR710): All components of this formulation are listed in the TSCA Inventory.

State Regulations:

California Proposition 65: This product does not intentionally contain any chemicals, which have been identified by the state of California to cause cancer, birth defects or other reproductive harm
Florida, Massachusetts, Minnesota, Pennsylvania and Washington Substance List:

| <u>Chemical Name</u> | <u>CAS #</u> | <u>% by Weight</u> |
|---------------------------------------|--------------|--------------------|
| 4, 4' Methylene bis(phenylisocyanate) | 01-68-8 | 40.0 Max |

Massachusetts, Michigan and Pennsylvania Substance List:

| <u>Chemical Name</u> | <u>CAS #</u> | <u>% by Weight</u> |
|------------------------|--------------|--------------------|
| Butyl Benzyl Phthalate | 85-68-7 | 70.0 Max |

16 - Other Information

Material Safety Data Sheet

MSDS No. 73-053A, 73-052, 73-052-5

Date Of Preparation: May 2, 2005

Revision: 0001

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: LMR - Liquid Mold Rubber - Part B

Manufacturer: Romanoff International, 9 Deforest St., Amityville, NY 11701

Phone (631) 842-2400, FAX (631) 842-0028

Emergency Contact: Chem-Tel

Domestic 800-255-3924

International 813-248-0585

Section 2 - Composition / Information on Ingredients

| Component | CAS Number | ACGIH TWA | Exposure Limits OSHA PEL | Weight Percent (%) |
|---|------------|-------------------------------|------------------------------|-----------------------|
| Butyl benzyl phthalate | 85-68-7 | None Established | None Established | 30-35 |
| New Jersey Trade Secret #221290880-5003P | - | None Established | None Established | 30-35 |
| Kaolin | 1332-58-7 | 2 mg/m ³ as dust | 15 mg/m ³ as dust | 15-20 |
| Silica, Quartz | 14808-60-7 | 0.1 mg/m ³ as dust | 50 mg/m ³ as dust | 15-20 |
| Titanium Dioxide | 13463-67-7 | 10mg/m ³ as dust | 15mg/m ³ as dust | 1-3 |
| Phenylmercuric neodecanoate | 26545-49-3 | 0.01 mg/m ³ | 0.01 mg/m ³ | 0.1 |

Section 3 - Hazards Identification

Potential Health Effects

Primary Entry Routes: Dermal

Target Organs: pancreas, liver, thyroid and eyes.

Acute Effects

Inhalation: Vapors, which are not significant unless heated or sprayed can cause irritation to respiratory tract.

Eye: May cause irritation, redness, tearing.

Skin: Contact will cause irritation and reddening swelling.

Ingestion: Effects are unknown.

Carcinogenicity: IARC lists Silica, quartz dust, as a probable carcinogen.

Medical Conditions Aggravated by Long-Term Exposure: Pre-existing skin disorders.

Chronic Effects of Overexposure:

This product contains an organo-mercury catalyst below the reportable level required by OSHA 1910.1200; however, due to the chronic toxicity of organo-mercury compounds careful handling of this product is required.

| HMIS | |
|------|---|
| H | 2 |
| F | 1 |
| R | 1 |

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air.

Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact: In case of skin contact, wash thoroughly with soap and water; remove contaminated clothing and launder before reuse; seek medical attention if rash develops.

Ingestion: Do not induce vomiting unless instructed by a physician. Contact physician immediately. *After first aid, get appropriate, paramedic, or community medical support*

Section 5 - Fire-Fighting Measures

Flash Point: >300 °F (150°C)

Flash Point Method: COC

Flammability Classification: Non-Flammable

Extinguishing Media: Water Fog, Dry Chemical, and Carbon Dioxide Foam

Unusual Fire or Explosion Hazards: None

Fire-Fighting Instructions: Fire fighters should wear self-contained breathing apparatus. Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.



Section 6 - Accidental Release Measures

Spill /Leak Procedures: Dike and contain spill; absorb or scrape up excess into suitable container for disposal. Stop or reduce discharge if it can be done safely.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - Handling and Storage

Handling Precautions: Minimize breathing of vapors and avoid prolonged or repeated contact with skin. Wear proper protective equipment. If ventilation is not sufficient, wear proper respiratory equipment. Use good general housekeeping procedures.

Storage Requirements: Store in cool dry, well-ventilated area.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls:

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Administrative Controls:

Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear an MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Protective Clothing/Equipment: Wear chemically protective gloves, boots, and aprons to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics

Section 9 - Physical and Chemical Properties

| | |
|--|---|
| Physical State: Liquid | Water Solubility: Negligible: |
| Appearance : White viscous liquid | Boiling Point: None (Polymeric Resin) |
| Odor : Characteristic odor | % Volatile: Nil |
| Vapor Pressure: None (Polymeric Resin) | Freezing/Melting Point: None Determined |
| Vapor Density (Air=1): >1 | Viscosity: 90 poise |
| Specific Gravity (H₂O=1, at 4 °C): 1.4 | Evaporation Rate: None (Polymeric Resin) |

Section 10 - Stability and Reactivity

Stability: This product is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization can not occur.

Chemical Incompatibilities: Strong acids and oxidizers.

Conditions to Avoid: Avoid contamination with water and other materials that react with amines.

Thermal Decomposition Products: Oxides of nitrogen, carbon monoxide and carbon dioxide

Section 11- Toxicological Information

Toxicity Data:

Acute Inhalation Effects:

None established

Acute Oral Effects:

None Established

Reproductive Toxicity: None Established

Mutagenicity: None Established

Teratogenicity: None Established

Sensitization: None Established

Section 12 - Ecological Information

None Established

Section 13 - Disposal Considerations

Disposal: This material contains a hazardous constituent as identified in RCRA, Title 40 CFR 261, Appendix VIII and must be disposed of in accordance with applicable Federal, state, and local regulations.

Section 14 - Transport Information

| DOT | IATA | IMDG |
|--|--|--|
| Shipping Name: Butyl Benzyl Phthalate Mixture (Greater than 100 pounds of Butyl Benzyl Phthalate) UN #: 3082 Hazard Class: 9 Label: Miscellaneous | Shipping Name: Butyl Benzyl Phthalate Mixture (Greater than 100 pounds of Butyl Benzyl Phthalate) UN #: 3082 Hazard Class: 9 Label: Miscellaneous | Shipping Name: Butyl Benzyl Phthalate Mixture UN #: 3082 Hazard Class: 9 Label: Marine Pollutant |

Section 15 - Regulatory Information

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

CERCLA Hazardous Substance (40 CFR 302.4) listed per RCRA, Sec. 3001; CWA, Sec. 311 (b)(4); CWA, Sec. 307(a), CAA, Sec. 112

| <u>Components That Require Reporting</u> | <u>RQ</u> | <u>% of Reportable Component</u> |
|--|-----------|----------------------------------|
| Butyl Benzyl Phthalate | 100 lbs. | 35.0 Max. |
| Mercury (as part of catalyst) | 1 lb. | 0.03 Max |

SARA Toxic Chemical (40 CFR 372.65):

| <u>Chemical Name</u> | <u>CAS #</u> | <u>% by Weight</u> |
|------------------------|--------------|--------------------|
| Butyl Benzyl Phthalate | 85-68-7 | 35.0 Max |

This product contains the following chemicals that are subject to release reporting requirements under section 313 of SARA Title III.

| <u>Chemical Name</u> | <u>CAS #</u> | <u>% by Weight</u> |
|------------------------|--------------|--------------------|
| Butyl Benzyl Phthalate | 85-68-7 | 35.0 Max |
| Mercury Compounds | - | 0.10 Max |

TSCA Inventory Status (40 CFR 710): All components of this product are listed on the TSCA inventory.

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): Not listed, Threshold Planning Quantity (TPQ)

State Regulations:

California Proposition 65: This product does not intentionally contain any chemicals, which have been identified by the state of California to cause cancer, birth defects or other reproductive harm.

Florida Right To Know, Substance List: Silica

Massachusetts Right To Know, Substance List: Butyl Benzyl Phthalate, Silica, Titanium Dioxide

Pennsylvania Right To Know, Substance List: Butyl Benzyl Phthalate, Kaolin. Silica,

Titanium Dioxide

Michigan Right To Know, Substance List: Butyl Benzyl Phthalate

Minnesota Right To Know, Substance List: Kaolin, Silica, Titanium Dioxide

Washington Right To Know, Substance List: Silica, Titanium Dioxide

16 - Other Information