

Safety Data Sheet

ITEM# 75-003-A

1. Identification

Product number

ITEM# 75-003-A

Product identifier

Dry Silicone Mold Release Spray

Supplier

Romanoff International Supply Corporation

9 Deforest Street

Amityville, NY 11701 US

Tel: 631-842-2400

Emergency telephone

CHEM TEL, ACCOUNT# MIS4594445

United States, Canada, Puerto Rico & U.S. Virgin Islands: 1-800-255-3924, Australia: 1-300-954-583, Brasil: 0-800-591-6042, China: 400-120-0751, India: 000-800-100-4086, Mexico: 800-099-0731
ALL OTHER COUNTRIES: 1-813-248-0585

Version#

01

LUBRICANT

Recommended use Recommended restrictions

None known.

2. Hazard(s) identification

Physical hazards

Flammable aerosols

Category 1

Health hazards

Serious eye damage/eye irritation

Category 2A

Specific target organ toxicity, single exposure

Category 3 narcotic effects

Aspiration hazard

Category 1

OSHA defined hazards

Not classified.

Label elements



Signal word

Hazard statement

Danger

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes serious eye irritation, May cause drowsiness or dizziness.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/face protection.

Response

If swallowed: Immediately call a poison center/doctor. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Do NOT induce vomiting. If eye irritation persists: Get medical advice/attention.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

Disposal

sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

Environmental hazards

Hazardous to the aquatic environment, acute Category 2

hazard

Hazardous to the aquatic environment, long-term hazard

Category 2

Hazard(s) not otherwise

classified (HNOC)

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name Acetone	Common name and synonyms	CAS number	%
Butane		67-64-1	20 - 40
Naphtha, (Petroleum), Hydrotreated	1	106-97-8	10 - 20
Light Propane		64742-49-0	10 - 20
Distillates (petroleum)		74-98-6	10 - 20
Hydrotreated Light		64742-47-8	2.5 - 10
n-Heptane		142-82-5	
Other components below reportable levels esignates that a specific chemical identity and/or percentage of composition ha			2.5 - 10 2.5 - 10

Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Skin contact Eye contact

Ingestion

Most important symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

General information

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Wash off with soap and water. Get medical attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

General fire hazards

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for A Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL		
	1	2400 mg/m3	The second secon
n-Heptane (CAS 142-82-5)	PEL	1000 ppm	
	1 22	2000 mg/m3	
Propane (CAS 74-98-6)	PEL	500 ppm	
= =		1800 mg/m3	
US. ACGIH Threshold Limit Value		1000 ppm	
Components			
	Туре	Value	
Acetone (CAS 67-64-1)	STEL	500 nam	
2.1	TWA	500 ppm	
Butane (CAS 106-97-8)	STEL	250 ppm	
n-Heptane (CAS 142-82-5)	STEL	1000 ppm	
	TWA	500 ppm	
JS. NIOSH: Pocket Guide to Chen	ical Hazarde	400 ppm	
Components	Type	14.4 (0)	
cetone (CAS 67-64-1)	Type	Value	
cetorie (CAS 67-64-1)	TWA	590 mg/m3	
utane (CAS 106-97-8)		250 ppm	
utane (CAS 106-97-8)	TWA	1900 mg/m3	
Hentana (CAS 140 as 5)		800 ppm	
Heptane (CAS 142-82-5)	Ceiling	1800 mg/m3	
		440 ppm	
	TWA	350 mg/m3	
opane (CAS 74-98-6)	TWA	85 ppm	
opane (OAS /4-98-6)		1800 mg/m3	
		1000 ppm	

Biological limit values

ACGIH Biological Expos	sure Indices				
Components	Value	Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)	25 mg/l		-pointen	Sampling Time	
* - For sampling details a		Acetone	Urine	*	

* - For sampling details, please see the source document.

Appropriate engineering

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates controls should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide

Individual protection measures, such as personal protective equipment

Eye/face protection

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other

Wear suitable protective clothing.

Respiratory protection

Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Aerosol.

Color

Not available.

Odor

Not available.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point Initial boiling point and boiling

Not available.

range

167.95 °F (75.53 °C) estimated

Flash point

-156.0 °F (-104.4 °C) PROPELLANT estimated

Evaporation rate

Not available.

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

1.9 % estimated

(%)

Flammability limit - upper

10.1 % estimated

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

Not available.

Vapor density

Not available.

Relative density

Not available.

Solubility(ies)

Solubility (water)

Not available.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

Not available.

Decomposition temperature

Viscosity

Not available. Not available.

Product name: 100 HEAVY DUTY 6% SILICONE LUBRICANT & RELEASE AGENT

Product #: 1000002368 Version #: 01 Issue date: 08-30-2018

Other information

Explosive properties

Not explosive.

Oxidizing properties

Not oxidizing.

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous reactions

Hazardous polymerization does not occur.

Conditions to avoid

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials

Acids. Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

Hazardous decomposition

No hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Causes serious eye irritation.

Ingestion

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness.

Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity

May be fatal if swallowed and enters airways. Narcotic effects.

Components Acetone (CAS 67-64-1)

Species

Test Results

Acute Dermal

LD50

Guinea pig

> 7426 mg/kg, 24 Hours

Rabbit

> 9.4 ml/kg, 24 Hours

> 7426 mg/kg, 24 Hours

> 9.4 ml/kg, 24 Hours

Inhalation

LC50

Rat

55700 ppm, 3 Hours

132 mg/l, 3 Hours

50.1 mg/l

Oral

LD50

Rat

5800 mg/kg

2.2 ml/kg

Butane (CAS 106-97-8)

Acute

Inhalation

LC50

Mouse

1237 mg/l, 120 Minutes

52 %, 120 Minutes

Rat

1355 mg/l

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

Acute

Dermal

LD50

Rabbit

> 2000 mg/kg

Product name: 100 HEAVY DUTY 6% SILICONE LUBRICANT & RELEASE AGENT

Product #: 1000002368 Version #: 01 Issue date: 08-30-2018

SDS US

5/11

Components	Species	Test Results
Inhalation		> 2000 mg/kg, 24 Hours
LC50		5-15, -11, 10, 10
2000	Rat	> 7.5 mg/l, 6 Hours
01		> 4.6 mg/l, 4 Hours
Oral LD50		ingri, 4 Hours
	Rat	> 5000 mg/kg
Naprillia, (Petroleum), Hyd	rotreated Light (CAS 64742-49-0)	> 3000 mg/kg
Acute	,	
Dermal		
LD50	Guinea pig; Rabbit	> 9.4 ml/lcm .04.11.
	Rabbit	> 9.4 ml/kg, 24 Hours
Inhalation		> 1900 mg/kg, 24 Hours
LC50	Rat	5000
		> 5000 mg/m3, 4 Hours
		> 4980 mg/m3
		> 4980 mg/m3, 4 Hours
		> 4.96 mg/l, 4 Hours
Oral		13700 ppm, 4 Hours
LD50	Rat	
1-Heptane (CAS 142-82-5)	ndi	4820 mg/kg
Acute		
Dermal		
LD50	Rabbit	
Inhalation	Παυσί	> 2000 mg/kg, 24 Hours
LC50	Rat	
Oral	Tal	> 29.29 mg/l, 4 Hours
LD50	Rat	
opane (CAS 74-98-6)	ııqı	> 5000 mg/kg
Acute		
Inhalation		
LC50	Mouse	
	Modse	1237 mg/l, 120 Minutes
	5.	52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
* Coting at 1	y be based on additional component data no	

Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization

Not a respiratory sensitizer.

Skin sensitization

This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

May be fatal if swallowed and enters airways.

Chronic effects

Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity

Toxic to aquatic life with long lasting effects.

C	to addate me with long lasting effects.			
Components		Species	Total	
Acetone (CAS 67-64-1)		•	Test Results	
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	0.4.0	
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	21.6 - 23.9 mg/l, 48 hours 4740 - 6330 mg/l, 96 hours	
Distillates (petroleum), Hyd	rotreated Light	t (CAS 64742-47-8)		
Aquatic		(6/10/04/42-4/-0)		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours	
-Heptane (CAS 142-82-5)		(Oncomynenus mykiss)		
Aquatic				
Fish	LC50	Mozambique tilapia (Tilapia mossambica)	375 mg/l, 96 hours	
Estimate 6				

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Acetone -0.24Butane 2.89 n-Heptane 4.66 Propane 2.36

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1

Subsidiary risk Label(s) 2.1

Packing group Not applicable. Special precautions for user Not available.

Special provisions N82 Packaging exceptions 306 Packaging non bulk None Packaging bulk None

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) 2.1

Packing group Not applicable. Environmental hazards

Yes **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Other information

Passenger and cargo

Allowed with restrictions. aircraft

Cargo aircraft only

Allowed with restrictions.

Packaging Exceptions

LTD QTY

IMDG

UN number UN proper shipping name

UN1950 **AEROSOLS**

Transport hazard class(es)

Class 2.1 Subsidiary risk

Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutant EmS

F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions Transport in bulk according to

LTD QTY Not established.

Annex II of MARPOL 73/78 and

the IBC Code

DOT





Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes Delayed Hazard - No. Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and

Acetone (CAS 67-64-1)

6532

Product name: 100 HEAVY DUTY 6% SILICONE LUBRICANT & RELEASE AGENT

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1)

35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1)

6532

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Naphtha, (Petroleum), Hydrotreated Light (CAS 64742-49-0)

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) n-Heptane (CAS 142-82-5) Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) n-Heptane (CAS 142-82-5) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) n-Heptane (CAS 142-82-5) Propane (CAS 74-98-6)

US. Rhode Island RTK

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2) Ethyl Benzene (CAS 100-41-4)

Listed: February 27, 1987

Listed: June 11, 2004 US - California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2) Toluene (CAS 108-88-3)

Listed: December 26, 1997

Listed: January 1, 1991 US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2)

Listed: December 26, 1997

International Inventories

Country(s) or region Australia	Inventory name	On inventory (yes/no)*
Canada	Australian Inventory of Chemical Substances (AICS) Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical	Yes
Furon	Substances (EINECS)	Yes
Europe Japan	European List of Notified Chemical Substances (ELINCS)	No
Korea	Inventory of Existing and New Chemical Substances (ENCS)	Yes
New Zealand	Existing Chemicals List (ECL) New Zealand Inventory	Yes
Philippines	\ \@	Yes
	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Product name: 100 HEAVY DUTY 6% SILICONE LUBRICANT & RELEASE AGENT

Country(s) or region

Inventory name

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

On inventory (yes/no)*

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

16. Other information, including date of preparation or last revision

Issue date

08-30-2018

Version #

01

Disclaimer

We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written

based on the best knowledge and experience currently available.

Revision information

Product and Company Identification: Alternate Trade Names