



SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

ROMANOFF
INTERNATIONAL SUPPLY CORPORATION

Page 1/7

780 investment with fiberglass


Revision 0

Revision date 2016-12-12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product name	780 investment with fiberglass
Product code	780 investment with f-g 121216 R212
1.2. Relevant identified uses of the substance or mixture and uses advised against	
Description	Foundry material.
1.3. Details of the supplier of the safety data sheet	
Company	Romanoff International Supply Corporation
Address	9 Deforest Street, Amityville, NY 11701 USA. Tel: 631-842-2400
Web	www.romanoff.com
Telephone	+1 (631) 842-2400
Fax	+1 (631) 842-0028
Email address of the competent person	sales@romanoff.com
1.4. Emergency telephone number	
Emergency telephone number	CHEMTEL, ACCOUNT #MIS4594445 COLLECT CALLS ACCEPTED
Company	USA, CANADA 1-800-255-3924 AUSTRALIA: 1-300-954-583 BRAZIL: 0-800-591-6042 CHINA: 400-120-0751 INDIA: 000-800-100-4086 MEXICO: 01-800-099-0731 ALL OTHER COUNTRIES: 1-813-248-0585

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture	
2.1.2. Classification - EC 1272/2008	Carc. 1A: H350; STOT RE 1: H372;
2.2. Label elements	
Hazard pictograms	This substance /mixture has been classified in accordance with the US Federal OSHA Hazard Communication Standard 29CFR 1910.1200. 
Signal Word	Danger
Hazard Statement	Carc. 1A: H350 - May cause cancer inhalation. STOT RE 1: H372 - Causes damage to organs (lungs) through prolonged or repeated exposure inhalation.
Precautionary Statement: Prevention	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

780 investment with fiberglass

Revision 0

Revision date 2016-12-12

2.2. Label elements

Precautionary Statement: Response	P264 - Wash (hands) thoroughly after handling.
	P270 - Do not eat, drink or smoke when using this product.
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P285 - In case of inadequate ventilation wear respiratory protection.
Precautionary Statement: Storage	P308+P313 - IF exposed or concerned: Get medical advice/attention.
	P314 - Get medical advice/attention if you feel unwell.
Precautionary Statement: Disposal	P405 - Store locked up.
	P501 - Dispose of contents/container to local and national regulations

2.3. Other hazards

Other hazards	Product contains crystalline silica.
----------------------	--------------------------------------

Further information

	Not applicable. PBT and vPvB assessment.
--	--

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
phosphate binder (proprietary)					1 - 10%	Xi; R36/38	
phosphate binder 2 (proprietary)					1 - 10%	Xi; R36/38	
Quartz		14808-60-7	238-878-4		1 - 10%	Xn; R48/20	
Magnesium Oxide		01309-48-4	215-171-9		1 - 10%	Xn; R20 Xi; R37/38	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
quartz (conc. >= 1.0%)		14808-60-7	238-878-4		50 - 60%	Carc. 1A: H350; STOT RE 1: H372;	
phosphate binder (proprietary)					1 - 10%	Skin Irrit. 2: H315; Eye Irrit. 2: H319;	
phosphate binder 2 (proprietary)					1 - 10%	Skin Irrit. 2: H315; Eye Irrit. 2: H319;	
Quartz		14808-60-7	238-878-4		1 - 10%	STOT RE 1: H372;	
silica (cristobalite conc. >= 1.0%)		14464-46-1	238-455-4		20 - 30%	Carc. 1A: H350; STOT RE 1: H372;	
synthetic vitreous fibers					0.5 - 1%		

Further information

	Full text for all Risk Phrases mentioned in this section are displayed in Section 16.
--	---

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash with soap and water.
Ingestion	Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause irritation to respiratory system.
Eye contact	May cause irritation to eyes.

780 investment with fiberglass

Revision 0

Revision date 2016-12-12

4.2. Most important symptoms and effects, both acute and delayed

Skin contact	May cause irritation to skin.
Ingestion	May cause irritation to mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention if irritation or symptoms persist.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention if irritation or symptoms persist.

SECTION 5: Firefighting measures**5.1. Extinguishing media**

	Use extinguishing media appropriate to the surrounding fire conditions.
--	---

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear suitable protective clothing.
--	--

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

	Avoid raising dust. Wear suitable respiratory equipment when necessary.
--	---

6.2. Environmental precautions

	No environmental requirements.
--	--------------------------------

6.3. Methods and material for containment and cleaning up

	Avoid raising dust. Clean the area using a vacuum cleaner. Transfer to suitable, labelled containers for disposal.
--	--

6.4. Reference to other sections

	See section [2, 8 & 13] for further information.
--	--

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

	Avoid raising dust. Ensure adequate ventilation of the working area. In case of insufficient ventilation, wear suitable respiratory equipment.
	Do not eat, drink or smoke in areas where this product is used or stored. Wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

	Keep containers tightly closed.
--	---------------------------------

7.3. Specific end use(s)

	Foundry material.
--	-------------------

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

	exposure limits - Crystalline Silica, Cristobalite - 0.025 mg/m ³ TWA ACGIH TLV (respirable fraction); 10 mg/m ³ / [2(% Silica + 2)] TWA PEL (respirable fraction).
	exposure limits - Crystalline Silica, quartz - 0.025 mg/m ³ TWA ACGIH TLV (respirable fraction); 10 mg/m ³ / (% Silica + 2) TWA PEL (respirable fraction).

780 investment with fiberglass

Revision 0

Revision date 2016-12-12

8.1.1. Exposure Limit Values

Quartz	WEL 8-hr limit ppm:	WEL 8-hr limit mg/m3: 0.3
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Protective clothing.
Eye / face protection	In case of splashing, wear:.. Approved safety goggles. safety glasses with side-shields.
Skin protection - Handprotection	Wear suitable gloves.
Respiratory protection	Suitable respiratory equipment.
8.2.3. Environmental exposure controls	Not normally required.
Occupational exposure controls	Appropriate local exhaust ventilation is required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Powder
Colour	Off white
Odour	Slight
pH	6 - 8
Melting point	No data available
Freezing Point	Not applicable.
Initial boiling point	Not applicable.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Relative density	2.6 (H2O = 1 @ 20 °C)
Fat Solubility	Not applicable.
Partition coefficient	No data available
Autoignition temperature	Not applicable.
Viscosity	No data available
Explosive properties	Not applicable.
Oxidising properties	Not applicable.
Solubility	Slightly miscible in water

9.2. Other information

Conductivity	No data available
Surface tension	No data available
Benzene Content	Not applicable.
Lead content	Not applicable.
VOC (Volatile organic compounds)	Not applicable.

SECTION 10: Stability and reactivity

10.1. Reactivity

	Not applicable.
--	-----------------

780 investment with fiberglass

Revision 0

Revision date 2016-12-12

10.2. Chemical stability	
	Stable under normal conditions.
10.3. Possibility of hazardous reactions	
	No Significant Hazard.
10.4. Conditions to avoid	
	Moisture.
10.5. Incompatible materials	
	No Significant Hazard.
10.6. Hazardous decomposition products	
	Hazardous Decomposition Products (silica): Crystalline silica will dissolve in hydrofluoric acid and produce silicone tetrafluoride. Reaction with water or acids generates heat.

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

Acute toxicity	Based on available data, the classification criteria are not met.
Skin corrosion/irritation	Prolonged or repeated exposure may cause irritation to skin and mucous membranes.
Serious eye damage/irritation	No irritation expected.
Respiratory or skin sensitisation	No sensitization effects reported.
Germ cell mutagenicity	No mutagenic effects reported.
Carcinogenicity	Known Human Carcinogens (Category 1).
Reproductive toxicity	No observed effect level. No observed effect concentration.
STOT-single exposure	No known adverse health effects.
STOT-repeated exposure	<p>Chronic effects</p> <p>Prolonged inhalation of respirable crystalline silica</p> <p>In 1997, the International Agency for Research on Cancer (IARC) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibers, 1997, Vol. 68, IARC, Lyon, France). In June 2003, the European Commission's Scientific Committee for Occupational Exposure Limits (SCOEL) concluded:</p> <p>"that the main effect in humans of the inhalation of respirable crystalline silica is silicosis. There is sufficient information to conclude that the relative lung cancer risk is increased in persons with silicosis (and apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk. Since a clear threshold for silicosis development cannot be identified, any reduction of exposure will reduce the risk of silicosis."</p> <p>(SCOEL SUM Doc 94-final on respirable crystalline silica, June 2003)</p> <p>There is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required (see Section 16).</p>
Aspiration hazard	No Significant Hazard.
Repeated or prolonged exposure	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.

SECTION 12: Ecological information**12.2. Persistence and degradability**

	No data is available on this product.
--	---------------------------------------

780 investment with fiberglass

Revision 0

Revision date 2016-12-12

12.3. Bioaccumulative potential

Does not bioaccumulate.

Partition coefficient

780 investment with fiberglass No data available

12.4. Mobility in soil

Not determined.

12.5. Results of PBT and vPvB assessment

Not determined.

12.6. Other adverse effects

Not applicable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of in compliance with all. local and national regulations.

Disposal methods

Contact a licensed waste disposal company.

Disposal of packaging

Empty containers can be sent for disposal or recycling.

SECTION 14: Transport information

Further information

The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations

U.S. FEDERAL REGULATIONS:

CERCLA 103 Reportable Quantity: 780 investment with fiberglass is not subject to CERCLA reporting requirements. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA TITLE III:

Hazard Category For Section 311/312: Chronic health

Section 313 Toxic Chemicals: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.

U.S. STATE REGULATIONS

California Proposition 65: This product contains the following substances known to the State of California to cause cancer: Crystalline Silica as Quartz and Cristobalite, < 95%.

INTERNATIONAL REGULATIONS:

Canadian Environmental Protection Act: All of the components in this product are listed on the

780 investment with fiberglass

Revision 0

Revision date 2016-12-12

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

	Domestic Substances List (DSL).
	Canadian WHMIS Classification: Class D Division 2A.

15.2. Chemical safety assessment

	No data is available on this product.
--	---------------------------------------

SECTION 16: Other information**Other information**

Text of risk phrases in Section 3	R20 - Harmful by inhalation. R36/38 - Irritating to eyes and skin. R37/38 - Irritating to respiratory system and skin. R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.
Text of Hazard Statements in Section 3	Carc. 1A: H350 - May cause cancer . STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure . Skin Irrit. 2: H315 - Causes skin irritation. Eye Irrit. 2: H319 - Causes serious eye irritation.

Further information

	<p>Training Workers must be informed of the presence of crystalline silica and trained in the proper use and handling of this product as required under applicable regulations.</p> <p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>
--	---