Indutherm MC60V Casting Kit

The **Indutherm MC60 V** has been developed with the user in mind for whom the MC 16 is too small but a simple machine from the large VC series (e.g. the VC 400) is too big or requires too much manual operation. This small-medium high-performance casting machine is ideal for jewellery alloys such as **gold**, **silver, copper and bronze, as well as for alloys of brass and aluminium.** Thanks to the vacuum and overpressure functions as well as the many automatic control features, the machine provides first class castings with very little work. The use of the included vibration technology when casting ensures better form filling, creating casts with greater, more consistent densities, higher elasticity and greatly reduced porosity.




Pouring off is simple and easy, and takes place using a 90° rotation of the casting unit.

\$23,995

۲

SKU#74-931





After pouring, the MC series automatically switches to overpressure to optimize the cast, designed specifically for delicate and filligree parts.





Indutherm MC60V

Max Power	3.5KW
Max Temperature	1300°C
Vibration Technology	Yes
Temperature Measurement	1300°C
Casting Volume	450g Au, 300g Ag
Maximum Flask Size	Up to 80/100mm W x 120mm H
Automatic Vaccum & Overpressure	Standard
Vacuum or Overpressure	-1 or +2 bar
Washing by Inert Gas	Standard
Power Supply	230V 1 Phase, 16 Amps
Dimensions and Weight	16" D x 16" W x 17.5"H - 70lbs







1-800-221-7448 sales@romanoff.com www.romanoff.com

۲

۲

۲

With St. Louis Mixers.

mixing chamber. A very

and pouring investment

important feature of

these units is mixing

under a controlled

This saves time by

combining mixing,

pouring and vacuuming

with vibration.

vacuum environment

you can automatically

mix and pour your

investment in an enclosed see through

SKU#74-931

SKU#76-113-4KG-P

Indutherm MC60V Casting Kit

The Romanoff Super **Blue Automatic** Furnace heats to 2000°F- ideal for lost wax casting and anealing applications. The digital Sentry Xpress controller includes temperature holds and multiple ramps. The 3-key digital controller is in the base. The front control panel is tilted for easy operation of the digital controller. Easily fits three standard casting flasks.



Max Temperature	2000°F
Fire Chamber Size	8.5"W x 9"H x 12"D
Flask Capacity	Three 4"x8.5" Flasks, 0.53 cubic ft
Power	19A, 110V, 2280W
Dimensions & Weight	14" x 22.5" x 20", 81lbs

Products Included in the Casting Kit

operations. Since it is user friendly, anyone can be trained in just a few minutes.		
Powder Capacity		4-KG
Flask Capacity		150x200mm Flask
Flask Plate Diameter		150mm
Dimensions		30 x 35 x 95 cm
Voltage		220V

RTER KIT 10 CFM Vacuum Max Wax Speed Hydro-Air Pressure estment Scale Platinum Wax Adjustable Sprue Pen Base Holder Pump Washer Gun 0-10 lbs Mushroom Base 5 Pack Stainless Steel Flask - 100 x 120mm 4" x 5" - 12ga 1: 76-066-Flask Saddle Adapter 2: 78-4507 3: 78-2506 Indutherm Outer Quartz Clear Crucible Shield 4: 78-2504 Gold/Silver Crucible Blue Tubing - 8 OD x 5mm ID 5: 005-013-M Sprue Base - Cone Style - 100mm / 4" 6: 76-019-I 7: 78-4502 Thermocouple Type-N Thermocouple Protection Tube 8: 78-4502-P Stainless Steel Flask 2 Stainless Steel Non-Asbestos 10 Non-Asbestos 14" Non-Asbestos Maun Sprue Cutter Air Filter & 8mm Fittings - 100x120mm / Flasks - 80x80mm / Paper Roll Paper Bases -Casting Gloves 6.5" / 165mm 9: n/a 4" OD x 3.25" ID Tongs for 100mm Flasks 2.5" x 1/16" x 75' 4"x5" - 12ga 3x3" - 12ga length 3 Liter Measuring Wax Sprue Rods Flask Saddle Ranson &

Pitcher + 250ML Graduated Cylinder

45 rods per lbs.





J-Formula "606" 2 Indutherm Cone Style Sprue Base with Blue Binder 80mm / 3"

Indutherm Sprue Base - Cone Style -100mm / 4"

Vacuum Investment

& Casting Machine 3 Way Valve





1-800-221-7448 sales@romanoff.com www.romanoff.com

Adapter for

80mm / 3" Flasks

۲

()

۲