

SKU: 68-5102

FlashForge WaxJet 510/530 XHD Support Material

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

- 1.1 Identification of the substance or preparation: FFMS3200 Support Material
- 1.2 Use of the substance / preparation: FFMS3200 Support Material is for use in the 510 Modeling System.
- 1.3 Company/undertaking identification:

Romanoff 3D LLC

9 Deforest Street, Amityville NY, 11701 USA

Phone: 631-573-7746

1.4 Emergency contact information (Chemtel: ACCOUNT #MIS4594445 COLLECT CALLS ACCEPTED)

USA, CANADA, PUERTO RICO & US VIRGIN ISLANDS:1-800-255-3924 AUSTRALIA: 1-300-954-583 BRAZIL: 0-800-591-6042 CHINA: 400-120-0751 INDIA: 000-800-100-4086 MEXICO: 01-800-099-0731

ALL OTHER COUNTRIES: 1-813-248-0585

2. HAZARDS IDENTIFICATION

2.1 Classification:

Not classified according to GHS, Regulation (EC) No. 1272/2008, 29 CFR 1910, Australian Dangerous Goods Code

2.2 Information pertaining to special dangers for human and environment:

Skin: Not expected to be absorbed through the skin. Wax, when heated, can cause skin burn.

Ingestion may cause nausea, diarrhea and/or stomach pain. Ingestion:

2.3 Label Elements

Regulation (EC) No. 1272/2008:

Hazard pictograms and signal word: None

Hazard statements: None



NFPA Ratings Hazardous Materials Identification System (HMIS):

(Degree of hazard: 0 = low, 4 = extreme); 0 = Minimal

1 = Slight Health 1 2 = Moderate Flammability 0 3 = Serious 0

Physical Hazards 4 = Severe

3. COMPOSITION/INFORMATION ON **INGREDIENTS**

3.1 Preparation related information

Description: Organic mixture 3.2 Dangerous components

Chemical name	CAS-No	EC-No	%	Classification	
				Regulation (EC) 1272/2008	Regulation 67/548/EEC, 1999/45/EC
Hydroxylated Wax	112-92-5	204-017-6	60%	-	=
Rosin resin	8050-09-7	650-015-00-7	40%	-	

4. FIRST AID MEASURES

- 4.1 General information:
- 4.2 In case of inhalation: Move affected person to fresh air. If respiratory irritation occurs, if breathing becomes difficult seek medical attention immediately.
- 4.3 In case of skin contact: If molten material gets on skin, cool rapidly with cold water. Do not attempt to peel material from skin. Use mineral oil to loosen the material. Seek medical attention for burns.
- 4.4 In case of eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if symptoms persist.
- 4.5 In case of ingestion: Ingestion is unlikely. If ingested, drink plenty of water and seek immediate medical attention. Do not induce vomiting.

5. FIRE-FIGHTING MEASURES

- 5.1 Suitable extinguishing media: Water mist, dry chemical, carbon dioxide, or appropriate foam.
- 5.2 Extinguishing media which must not be used for safety reasons: -
- 5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases: Thermal decomposition products can include CO2, CO and smoke.
- 5.4 Special protective equipment for fire-fighters: Use self-contained breathing apparatus. Use water spray to keep fire-exposed containers cool. Dust is not expected to be generated in the event of a fire.

6. ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions: Keep unnecessary personnel away. Wear appropriate protective equipment and clothing, including a ground strap, during clean up.
- 6.2 Environmental precautions: Stop the flow of material, if this is without risk. Ventilate contaminated area. Eliminate sources of ignition. Avoid the generation of dusts during clean up.
- 6.3 Methods for cleaning up: If material is molten, allow it to freeze before clean up. Scrape the material loose from the floor if necessary and vacuum or sweep the solid material into a closed container. Use internally and externally explosion-proof vacuum equipment with appropriate electrical classification per National Electrical Code, Article 502 or use non-sparking tools. Avoid the generation of dusts during clean up. Place material in an appropriate container for disposal.

7. HANDLING AND STORAGE

- 7.1 Handling: No special measures necessary in normal use of product.
- 7.2 Storage: Keep this material in a cool (<35 °C (95 °F)), dry, well-ventilated place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Exposure limit values:

General product information: No occupational exposure limits (PEL/TWA) have been established for this product.

8.2 Exposure controls

Technical measures to prevent exposure: Use local exhaust ventilation. Instructual measures to prevent exposure: When using, do not eat, drink or smoke. Wash hands after handling and before eating, smoking and using the lavatory and at the end of the day.

Personal protection equipment: Respiratory protection: If ventilation cannot effectively keep vapor concentrations below established limits, appropriate certified respiratory protection must be provided (e.g. 3M 6000 with organic vapor cartridge A2 or half mask 3M 4251). Hand protection: Use impervious nitrile gloves. Eye protection: Wear chemical goggles Body protection: Use apron.

9. PHYSICAL AND CHEMICAL PROPERTIES 9.1

Appearance: Physical state: Solid Colour: White Odour:

Mild

9.2 Important health, safety and environmental information

Safety relevant basic data

pH (20°C):

Melting point/range (°C): Boiling point/range (°C):

NA Flash point (°C): 55-65°C Ignition temperature (°C): NA Vapour pressure (°C):

185°C (COC) Density (g/cm3):

NA Bulk density (kg/m3): NA Water solubility (20°C in q/l): 0.80-0.91 Partition coefficient: NA n-Octanol/Water (log Po/w): insoluble Viscosity, dynamic (mPa s): NA Dust explosion hazard: NA **Explosion limits:** 12 (90°C)

NA NA

10. STABILITY AND REACTIVITY

- 10.1 Conditions to avoid: -
- 10.2 Materials to avoid: Avoid strong oxidizing agents.
- 10.3 Hazardous decomposition products: Carbon dioxide, carbon monoxide and other toxic fumes can be released at high temperatures or upon burning.

11. TOXICOLOGICAL INFORMATION

11.1 Toxicokinetics, metabolism and distribution: NA

11.2 Acute effects (toxicity tests)

Component	LD50 Oral	LD50 Dermal
Hydroxylated Wax	20`000 mg/kg (rats)	NA
Rosin resin	2800 mg/kg (rats)	2000 mg/kg (rats)

Irritant and corrosive effects: NA Irritation to respiratory tract: NA

Sensitisation: NA

11.3 Experiences made in practice

Observations relevant to classification: -

Other observations:-

11.4 General remarks:

Carcinogenicity: None of this product's components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP

12. Ecological information

12.1 Ecotoxicity: The aquatic toxicity of the product is unknown; however based on the components, it is predicted that the product is not harmful to the aquatic environment.

Component Analysis - Ecotoxicity - Aquatic Toxicity:

Component	Data
Hydroxylated Wax	LC50 (48h) - 1700 mg/l (daphnia) EC50 (96h) – 235 mg/l (Scenedesmus subspicatus (algae)
Rosin resin	LC50 (96h) - 60.3 mg/l (Zebrafish)

- 12.2 Mobility: No information available for product.
- 12.3 Persistence and degradability: No information available for product.
- 12.4 Results of PBT assessment: No information available for product.
- 12.5 Other adverse effects: No information available for product.
- 12.6 Further ecological information: The ecological assessment of this material is based on an evaluation of its components. This product is classified as not dangerous to the environment.

13. DISPOSAL CONSIDERATIONS

- 13.1 Appropriate disposal / Product: Avoid disposal. Attempt to utilize preparation completely. Prior to disposal of unused preparation, consult an approved waste disposal operative to ensure regulatory compliance.
- 13.2 Waste codes / waste designations according to EWC / AVV:

13.3 Appropriate packaging:

13.4 Additional information:

14. TRANSPORT INFORMATION

14.1 Land transport (ADR/RID/GGVSE): Not Regulated

Official transport designation:

Class:

Classification Code:

UN-No.:

Packing group:

Hazard label:

Tunnel restriction code:

Special provisions:

14.2 Sea transport (IMDG-Code/GGVSee): Not Regulated

Proper Shipping Name:

Class:

UN-No.:

Packing group:

EmS:

Marine Pollutant:

Special provisions:

14.3 Air transport (ICAO-IATA/DGR): Not Regulated

Proper Shipping Name:

Class:

UN-No.:

Packing group:

Special provisions:

15. REGULATORY INFORMATION

15.1 EU regulations

EINEC/ELINCS/NLP: All materials are listed

REACH Annex XVII: None listed

15.2 National EU regulations

Wassergefährdungsklasse - German Water Hazard Class (WGK): WGK1 (low hazard to waters)

15.3 US FEDERAL

TSCA: All materials are listed on the TSCA Inventory or are not subject to TSCA requirements:

California Proposition 65: This product does not contain chemicals which are known to the state of California to cause cancer, birth, or any other reproductive defects.

15.4 Australian regulations

SUSDP, Industrial Chemicals Act 1989:

Australian Inventory of Chemical Substances, AICS: Listed

15.5 Japanese regulations

Chemical Risk Information platform (CHRIP):

Industrial Health and Safety Law

Hazardous material

Organic solvent poison prevention rule

Ordinance on prevention of hazard due to specified chemical substances

Lead Poisoning Prevention Rule

Poison and Deleterious Substance Control law

PRTR and Promotion of Chemical Management law (PRTR Law)

Fire Services Act

Explosives Law

High pressure gas safety law

Export Trade Control Order

Waste Disposal and Public Cleaning Law

Listed not applicable not applicable not applicable not applicable not applicable not applicable no components not applicable not applicable not applicable not applicable applicable. Before disposal, consult an approved waste disposal operative to ensure regulatory compliance.

16. OTHER INFORMATION SDS Creation

Date: October 31, 2016

www.sz3dp.com [CH] www.flashforge.com [EN] 0086-571-89774128

DISCLAIMER OF LIABILITY: The following supersedes any related provision in your company's forms, letters, and agreements from, by or with Flashforge. Flashforge makes no warranty, whether expressed or implied, including warranties of merchantability or of fitness for a particular purpose for this product. No statements or recommendations contained in the product literature are to be construed as inducements to infringe any relevant patent now or hereafter in existence. Under no circumstances shall Flashforge be liable for incidental, consequential, special, or other damages from alleged negligence, breach of warranty, strict liability or any other theory, arising out of the manufacture, use, sale, or handling of this product. In no event shall the liability of Flashforge for any claims arising out of the manufacture, use, handling, or sale of its products exceed an amount equal to the buyer's purchase price.

The contents of this safety data sheet are subject to change without notice. Zhejiang Flashforge 3D Technology co, .Ltd. recommends that you periodically check www.sz3dp.com or www.flashforge.com to make sure you are using the most current safety data sheet.

© Copyright 2016-2017 by Zhejiang Flashforge 3D Technology co, .Ltd. All rights reserved. Flashforge is registered trademarks of Zhejiang Flashforge 3D Technology co, .Ltd.

The Flashforge logo is a trademark of Zhejiang Flashforge 3D Technology co, .Ltd.